Product Manual

E_UHADD-25W

Data Sheet

Wide voltage input,isolated,voltage regulator,double output



UL 62368-1 EN 62368-1 IEC 62368-1 RoHS

Product Series

Product Series	Temperature Range	Isolated Voltage	Package
E_UHADD-25W	-40℃～+105℃	1500VDC	DIP

Features

- Efficiency up to 89%
- Isolated voltage 1500VDC
- Sustainable short circuit
- Input under-voltage protection,output over-voltage protection,output over-current protection
- Black aluminum housing and potting compound meet the UL94 V-0 standards

Applications

- Industrial control systems
- Data communication systems
- Distributed power control systems
- Digital and analog hybrid systems
- BMS systems, instrumentation
- Distribution terminal,etc.
- ……

Product Model

Part Number	Certification	Input Voltage (VDC)		Output		Full Load Efficiency (%,Min/Typ)	Maximum Capacitive Load (μF)
		Nominal (Range)	Max.(1)	Nominal Voltage (VDC)	Current (mA) (Min./ Max.)		
E2415UHADD-25W	UL/EN/IEC	24(9-36)	40	±15	0/±833	87/89	600

Note:(1)The input voltage must not exceed the specified range value, otherwise it may cause permanent irreparable damage.

Limit Characteristics

Parameter	Conditions	Min	Typ	Max	Unit
Input Surge Voltage (1s，max)	24VDC input	-0.7	--	50	VDC
Lead Soldering Temperature	1.5mm from case,10s	--	--	300	℃
Hot Plug	--	Unavailable			

Input Characteristics

Parameter	Conditions		Min	Typ	Max	Unit
Input Voltage Range	24VDC input		9	24	36	VDC
No Load/Full Load Input Current	24VDC input		--	12/940	25/960	mA
Input Under Voltage Protection	24VDC input	Module on	--	8	9	VDC
		Module off	6	7.2	--	
Ctrl	Module on		Ctrl is floating or connected to TTL high level (3.5-12VDC)			
	Module off		Ctrl connected to GND or low level (0-1.5VDC)			
	Input current when turned off		--	0.3	1	mA
Input Filter			π type filter			

Output Characteristics

Parameter	Conditions		Min	Typ	Max	Unit
Line Regulation	Full load,input voltage from low to high	Positive output	--	±0.2	±0.5	%
		Negative output	--	±0.5	±1.0	
Load Regulation(1)	Nominal input voltage, load varies from 10% to 100%	Positive output	--	±0.5	±1	
		Negative output	--	±0.5	±1.5	
Cross Regulation	Dual output,main channel at 50% load, auxiliary channel at 10% to 100% load		--	--	±5	
Output Voltage Accuracy(2)	Load is from 10% to 100%		--	±1	±3	
Temperature Drift Coefficient	100% load		--	--	±0.03	%/℃
Output Ripple (3)	20MHz bandwidth		--	100	200	mVp-p
Output Noise(3)			--	100	200	mVp-p
Transient Recovery Time	Load step change 75%-50%-75%		--	300	500	μs
Transient Response Deviation			--	±3	±5	%
Over-Voltage Protection	Input voltage range		110	--	160	%Vo
Over-Current Protection(4)			110	--	180	%Io
Output Short-Circuit Protection			Sustainable short circuit, self-recovery			

Note:(1) Under 0%-5% load condition, the maximum output voltage accuracy is ±4%.

(2) When tested under 0%-100% load operating conditions, the load regulation specification is ±3%.

(3) The output ripple & noise under 0%-5% load is≤250mV;The ripple and noise are measured using the parallel- line test method.

(4)Over-current protection operates in hiccup mode.

General Characteristics

Parameter	Conditions	Min	Typ	Max	Unit
Isolation Voltage	Input-output, time 1 minute, leakage current less than 1mA	1500	--	--	VDC
Isolation Resistance	Input-output,isolation voltage 500VDC	1	--	--	GΩ
Isolation Capacitance	Input-output,100kHz,0.1V	--	2000	--	pF
Switching Frequency	Nominal input voltage, 100% load	--	300	--	kHz
MTBF	MIL-HDBK-217F@25℃	1000	--	--	k hours
Package Size	--	25.40×25.40×11.80			mm
Package Material	--	Metal shell			

Note:This type of product uses light load frequency reduction technology, the switching frequency is the test value when the full load output, when the load is less than 40%, the switching frequency decreases with the load.

Environmental Characteristics


Parameter	Conditions	Min	Typ	Max	Unit
Operating Temperature	See the ambient temperature derating curve for details	-40	--	+105	℃
Storage Temperature	--	-55	--	+125	
Casing Temperature Rise	Ta=25℃	--	40	--	
Storage Humidity	No condensation	--	--	95	%
Cooling Method		Natural air cooling			
Vibration		5-200Hz, 5G, 0.75mm. along X, Y and Z			

EMC Characteristics


EMI	CE	CISPR32/EN55032 CLASS B(Figure 2-②)	
	RE	CISPR32/EN55032 CLASS B(Figure 2-②)	
EMS	ESD	IEC/EN 61000-4-2 Contact±4kV	Perf.Criteria B
	RS	IEC/EN 61000-4-3 10V/m	Perf.Criteria A
	EFT	IEC/EN 61000-4-4 ±2kV(Figure 2-①)	Perf.Criteria B
	Surge	IEC/EN 61000-4-5 ±2kV(Figure 2-①)	Perf.Criteria B
	CS	IEC/EN 61000-4-6 3Vr.m.s	Perf.Criteria A

Note: Unless specified specially, parameters in this manual are measured under the conditions of 25℃, 40%~75% humidity, input nominal voltage and rated output load.


Product Characteristic Graph



Temperature Derating Graph




Efficiency VS load(Nominal input voltage)



Eifficiency VS input voltage(Full load)


Outline and Footprint Dimensions

Mechanic Size



Notes：
Unit：mm(inch)
Unlabeled tolerance：±0.5(±0.010)

PCB Silkscreen Diagram



Note：Grid distance：2.54×2.54mm

Pin Function Description

Pin	Funtion
1	Vin
2	GND
3	+Vo
4	0V
5	-Vo
6	Ctrl

Pack Instruction

Carton Size：L×W×H=269×254×127mm
144pieces/carton

Circuit Design and Application

1. Recommended circuit




Figure 1 Recommended circuit




Figure 2 EMC recommended circuit

2. Application circuit parameters

In order to further stabilize the input power supply, a capacitor Cin, is added at the input end; In order to reduce the output ripple and noise, it is necessary to add a capacitor Cout at the output end. Note that the output capacitance cannot exceed the maximum capacitive load. Excessive output capacitance may easily lead to poor startup of the power module. Recommended external capacitance values are shown in Table 1.

Table 1 The reference value of the external capacitor

Vin(VDC)	Cin(μF)	Vo(VDC)	Cout1/Cout2 (μF)
24	100	±15	10

Typical recommended circuit for EMC

Table 2 Recommended EMC external circuit parameters

Model	Vin：24VDC
FUSE	Select according to the actual input current of the customer
C0	470uF/50V
C1	470uF/50V
C2	4.7uF/50V
C3	10uF/50V
Cout1	Refer to Table 1
Cout2	
CY1	1nF/2KV
CY2	1nF/2KV
LCM1	470uH

3. Load requirements

In order to ensure efficient and reliable operation of the module, it is recommended that the output load should be between 5% and 100% of the rated power.

Guangzhou ZHIYUAN Electronics Co.,Ltd.
Service Hotline: 400-888-4005
E-mail：power.sales@zlg.cn
Website：http://www.zlg.cn
Special statement：Guangzhou ZHIYUAN Electronics Co., Ltd. reserves all rights.
Without our consent, our company improperly uses our datasheet, and our company reserves the right to pursue its legal responsibility.The datasheet will be updated without notice. If you need to check the latest version of the information, please visit our official website or contact our personnel for it.